

## HORIZONTAL DOUBLE SCISSOR LIFT TABLE

— PARALLEL LIFT FUNCTION

— LARGE LOAD AREA

— POWERFUL



### LIFT SOLUTIONS CAN BE FOUND AT EDMOLIFT

To handle goods that are both heavy and long you require a lift table with special properties. With EdmoLift's horizontal double scissor you have the solution at hand. The lift platform is equipped with a combination of two pairs of EdmoLift scissors to obtain the desired lift range and length of the lift table. Lift manoeuvres of the two pairs of scissors are mechanically controlled to achieve a parallel lift operation.

EdmoLift's horizontal double scissor makes it possible to handle bulky goods in a safe and effective way. With a variety of performances and models we offer a very wide range. The load capacity is between two and ten metric tons, the lift range varies between 820 mm and 2000 mm and the size of the lift table can be as large as 6200 x 1500 mm.

The lift table can be supplied in a variety of different colours designed specifically to suit the wishes of the customer, with a host of accessories and control alternatives. A number of models are available in a more hardwearing format especially suited to intensive operations. Functionality of the product can be increased by way of various accessories such as a mechanical stop and a foot control.

For more information, see our product leaflet "Accessories".

At EdmoLift you can find solutions for your lifting problems.

### PRODUCT FEATURES

- Load capacity max 10 000 kg.
- Lift platform length from 2600 mm to 6200 mm as a standard model.
- Comprehensive program of accessories and possibilities for customizing.
- Complies with European safety standard EN 1570-1 – CE certified.
- 24 V DC control unit and operating device with deadman's switch.
- IP54 approved electrical system.
- Safety spacing between all moving parts.
- Overload protection.
- Adjustable trap prevention safety trip bars on all four sides of the platform.
- The table is equipped with hose burst valves and mechanical locks for servicing and maintenance.
- Maintenance-free bearing surface.
- PLC control with possibility to program various functions is included for the standard model. PLC control enables customization for specific requirements.
- User manual in 20 different languages.

# HORIZONTAL DOUBLE SCISSOR LIFT TABLE



## PRODUCT INFORMATION

Model	Art.no	Capacity kg	Lift stroke mm	Closed height mm	Length mm	Width mm	Lift time sec	kW	Weight incl. packaging	Notes
TLH 2000	32930	2000	820	180	2600	800	30	0,75	350	
TLH 4000	33115	4000	820	200	2600	800	35	1,5	450	
TBH 4000	603261	4000	1000	230	3000	1000	40	1,5	490	
TMH 3000	33147	3000	1100	230	3400	900	35	1,5	700	
TMH 6000	33176	6000	1100	250	3400	900	55	1,5	740	
TMH 10000*	33902	10000	1100	300	3400	900	64	3,0	1100	
TAH 2000	33885	2000	1300	200	4000	800	32	1,5	600	
TAH 4000	34395	4000	1300	230	4000	900	45	1,5	800	
TAH 8000	33890	8000	1300	350	4000	1200	53	3,0	1300	
TSH 4001	610970	4000	1500	250	4400	1200	55	1,5	1036	
TSH 8000	33495	8000	1500	350	4400	1200	53	3,0	1360	
TTH 6000	32885	6000	1700	300	5000	1300	53	3,0	1400	
TTH 10000	33600	10000	1600	450	5000	1300	75	3,0	2215	
TPH 6000*	516158	6000	2000	400	6000	1500	37	5,5	2100	
TPH 10000*	33555	10000	2000	500	6000	1500	72	4,0	3240	

\*External powerpack without cover.

### CE- or Type 2B declaration

We construct and manufacture our lift tables and lift trolleys in accordance with the basic requirements in the Lift table standards EN 1570-1 and the Lift trolley standards SS-EN ISO 3691-5:2014. We comply with the requirements in accordance with Machine, Low voltage and the EMC directive. The products are delivered after being tested with CE certification and the assurance of agreement or in certain cases the manufacturer's Type 2B declaration.



EdmoLift AB  
Jägaregatan 11  
SE-871 42 HÄRNÖSAND  
SWEDEN

Tel. +46 (0) 611 - 837 80  
Fax. +46 (0) 611 - 511 580  
E-mail: info@edmolift.se  
Org. no.: 556241-1222

*EdmoLift*®  [www.edmolift.se](http://www.edmolift.se)